

AMENDMENTS TO THE CLAIMS

1. (Previously Presented) An apparatus for randomly outputting data stored sequentially in a memory, comprising:
 - means for generating a first index associated with a location in said memory;
 - means for comparing a reference parameter representative of the size of a block of input data stored in said memory to said first index;
 - means for outputting data stored in said memory location if said first index is less than or equal to said reference parameter; and
 - means for generating a second index if said first index is greater than said reference parameter.
2. (Cancelled)
3. (Original) The apparatus of claim 2, wherein said means for generating said first index comprises an index generator for generating said first or second index upon input of a primary or a secondary control signal, respectively.
4. (Original) The apparatus of claim 3, wherein said primary control signal is a signal periodically received by said means for generating said first index to initiate the generation of said first index.
5. (Previously Presented) The apparatus of claim 4, wherein said secondary control signal is a signal generated by said apparatus if said first index is greater than said reference parameter and received by said means for generating said second index to initiate the generation of said second index.
6. (Previously Presented) The apparatus of claim 5, wherein said means for comparing comprises a comparator for receiving said index from said first index generator and said reference parameter and outputting said secondary control signal if said reference parameter is less than or equal to said first index.

7. (Original) The apparatus of claim 6, wherein said means for outputting data, comprises an address generator for generating a memory output command upon input of a third control signal.

8. (Original) An apparatus for randomly outputting data stored sequentially in a memory, comprising:

a delay for receiving a first control signal at a first time period, outputting a second control signal at a second time period, and outputting a third control signal at a third time period;

an index generator for receiving one of said first control signal and a fourth control signal and outputting an index upon receipt of said first or fourth control signal, said index representing a location in said memory; and

a comparator for comparing said index to a reference parameter representative of the size of said data stored in said memory, and outputting upon receipt of said second control signal to said index generator said fourth control signal if said index is greater than said reference parameter.

9. (Original) The apparatus of claim 8, wherein said third time period is greater than said second time period and less than said first time period.

10. (Original) The apparatus of claim 9, further comprising an address generator for receiving said index, and outputting to said memory a memory address represented by said index upon receipt of said third control signal.

11. (Original) The apparatus of claim 10, wherein said memory outputs data located at said memory address.

12. (Cancelled)

13. (Original) An interleaver under control of a controller and having an

address generator for outputting an address to a memory, said memory sequentially storing input data and outputting data stored at said address upon receipt of said address, said controller determining a data size of said input data, comprising:

a delay for receiving a primary index enable signal and outputting a comparator enable signal at a first time period, and outputting an address generator enable signal at a second time period;

an index generator for receiving one of said primary index enable signal and a secondary index enable signal, and outputting an index upon receipt of said primary index enable signal or said secondary index enable signal; and

a comparator for comparing upon receipt of said comparator enable signal said index and said data size and outputting said secondary index enable signal if said index is greater than said data size;

wherein an input of said address generator is connected to the output of said index generator, and outputs upon receipt of said address generator enable signal a memory address associated with a most recently generated index.

14. (Previously Presented) An apparatus for randomly outputting data stored sequentially in a memory, comprising:

a delay for receiving a first control signal at a first time period, outputting a second control signal at a second time period, and outputting a third control signal at a third time period;

an index generator for receiving one of said first control signal and a fourth control signal and outputting an index upon receipt of said first or fourth control signal, said index associated with a location in said memory; and

a comparator for comparing said index to a reference parameter representative of the size of said data stored in said memory, and outputting upon receipt of said second control signal to said index generator said fourth control signal if said reference parameter is greater than said index.

15. (Previously Presented) The apparatus of claim 14, wherein said third time period is greater than said second time period and less than said first time period.

16. (Previously Presented) The apparatus of claim 15, further comprising an address generator for receiving said index, and outputting to said memory a memory address represented by said index upon receipt of said third control signal.

17. (Previously Presented) The apparatus of claim 16, wherein said memory outputs data located at said memory address.